

Plunger Ace No. 51

(Non-Graphite plunger tip lubricant)

Plunger Ace No. 51 is non-graphited, milk-yellow color plunger tip lubricant, and it has an adequate viscosity for automatic application.

Plunger Ace No. 51 provides a heat resistive protective film on all the moving parts operating at high temperature, and permits operation of the injection system at maximum efficiency.

Performance Benefits

1. Very economical, as a special effort is made to minimize excess run-off
2. Will not stain castings and keep the workshop clean.

Typical Properties

Appearance: Milk-yellow
Specific Gravity(15°C): 0.98
Viscosity(25°C): 2000Mps

Use

1. Plunger Ace No.51 is generally used in automatic lubricators
2. When using in an automatic lubricator, remove the cap and insert the intake pipe.
3. If an exclusive container is used for the system, be careful when you replenish the container with the lubricant not to mix in dust or other foreign materials, which might later become a serious problem.
4. Plunger Ace No. 51 is usually used without being diluted, but if spray application is desired, it can be diluted with kerosene until its viscosity becomes low enough to spray

Storage

Products should be stored on their sides in a clean, dry place and protected from extremes of temperature.

Health and Safety

Under normal conditions of use is not known to offer any serious health hazard. We would however, recommend good standards of industrial hygiene are observed when handling this product.

Package

18 kilogram pail /180 kilogram drum